



DUC

contact@duc-helices.com - www.duc-helices.com

New propeller FLASHBLACK In-Flight Adjustable propeller

 \bigcirc

 \bigcirc

 (\mathbf{O})

 \bigcirc

0

VG-H2A



Propellers

ISO 9001 **BUREAU VERITAS** ertification

contact@duc-helices.com - www.duc-helices.com

FLASHBLACK

In-Flight Adjustable propeller

Description

In-flight adjustable propeller with carbon/titanium blade and carbon hub Propeller weight extremely low; Titanium bolts Management of the pitch by "Constant speed" box & Visual indicator in flight Wide range of pitch variation & Safety stops small/large pitch Optimized performance for all phases of flight Hydraulic power with manual or electric control Low consumption & noise reduction Innovative high-precision manufacturing

Characteristics

Relices Propellers

- Tractor; 2-blade or 3-blade
- Propeller weight: 4.9kg in 2-blade & 6.5kg in 3-blade
- Pitch angle adjustable, amplitude max. : 23°
- Compatible with hollow shaft engine (Rotax 912S, 912iS, 914)
- Diameters Ø1520 to Ø1900mm (Ø60" to Ø75")
- Shielding leading edge in Inconel®

> Version

BASE: 2-blade / 3-blade FLASHBLACK prop. (5.9 & 7.5kg) 5834/6968€HT included Pitch indicator & Hydraulic setting wheel CONSTANT SPEED: Hydraulic pump & Constant Speed box (+0.74kg) +949 €HT



DH_FSH-PV_CM_02_D





